

Nice

Swing Gate Operator 1724

Blue
BUS



12
volt

120VAC powered 12VDC Linear Actuator Operator for swing gates up to 400lbs weight and 14 ft length
Recommended for residential applications
Solar compatible



Nice OXI/A Receiver and ABF/A Antenna Kit Included.

***Battery Backup included (2-7aH batteries)**

Versatile: Add the 512-2 Actuator to convert the 1724 to a dual gate system. 512-2 comes with 42 ft harness.

Powered by: Two 12V batteries kept charged by an AC power supply connected to a 120 VAC power source.

Reliable in any condition: In the event of electrical power outage, fully charged batteries will provide up to 200 cycles* on a basic system before requiring a recharge.

**Amount of cycles depends on consumption of attached accessories and duration of power outage*

The 1724 series uses the advanced **1050 control board** offering:

- LCD display for easy programming, diagnosing and troubleshooting
- Includes OXI/A receiver and ABF/A antenna kit
- Supports up to 1000 Inti or Era One remotes with rolling-code security
- Smart battery charging management
- Integrated 7 day programmable timer
- Surge protection
- Nice BlueBUS 2-wire technology self-identifies monitored photo eyes

Quality and durability: Engineered for durability and resistance to harsh environmental conditions. The control box is made from shatter resistant polycarbonate while the actuator housing is made up of two tough aluminum shells with environmentally friendly polyester paint that resists fading, chips, and scratches.

This system has a **sleek look** and an accessible compartment for easy installation and maintenance.

The 1724 actuators have an **external quick release** with keyed access for security.

Single or dual gate applications

Model	Description	Approvals
1724	Operator kit, 12VDC, 120VAC charged, swinging gates up to 14 ft, 400 lb, includes MB1050 and 512-1, UL325 6th Edition Compliant	ETL
512-2	Actuator kit, includes 42 ft harness and mounting hardware, use with 1724 for dual gate applications	

Technical Specifications

Model	1724
Electrical data	
Voltage Input	120VAC
Operating Voltage	12VDC
Idle Current	10mA
Performance data	
Rate of Travel	14 - 16 seconds to 90° open
Dimensions and general data	
Temperature Rating	-4° to 150° F (-20° to 65° C)
Dimensions - Control box	15.5w x 14h x 8d inches
Dimensions - Actuator	38 length x 4.5h x 4.1d inches



Contact Nice/HySecurity Regional Sales Manager for an operator/parts distributor near you.
phone **210-545-2900** | **800-226-0178** | www.niceforyou.us | orders@niceforyou.com
phone **253-867-3700** | **800-321-9947** | www.hysecurity.com | orders@hysecurity.com